



Translucent



REACH compliant



COLD

Cold-cut, crush-cut or ultrasonic



Manufactured in the EU

TECHNICAL PROPERTIES

Fabric Characteristic	Standard	
Composition	-	100 % PES
Weight (g/ m ²)	EN 12127	263 ± 5 %
Thickness (mm)		0.42 ± 5 %
Light fastness (Xenotest grade)	ISO 105 B02:2002	6 - 7
Roll size		Roller : Width 270 cm Length 37 m

Environmental & health properties

Formaldehyde-free and lead-free
Halogen-free
Oeko-tex standard 100 certified, which assures that no harmful substances are used during its production process.

Manufacturing properties

Always store rolls horizontally
Cold-cut, crush-cut or ultrasonic

Manufacturing direction:
Blinds can be manufactured 'drop to length' or railroaded, BUT the picture looks different if you manufactured in one direction or other

Manufacture panel blinds only 'drop to length'



Maintenance

Do not wash
Do not rub
Do not steam
Wipe gently with a wet sponge
Vacuum clean for regular maintenance



SUN CONTROL PROPERTIES

Colour	% Tv	% Rv	% Av
Beige	10	46	44
Off White	22	67	11
Sand	7	37	56



Check availability color and pattern model

All specifications are based on average values and may deviate. The values are given for guidance and are not contractual.
Subject to technical modifications