

Product Specifications	Standard	Rolls & Tiles (Rolls only for corridors)	Raised Access Floor Tiles (Square and Plank)
<b>Composition</b>	-	75%vinyl + 25% polyester + backing 100% vinyl	75%vinyl + 25% polyester + backing 100% vinyl
<b>Weight (g/m²) (oz/sq ft)</b>	ISO 8543:1998	3100 g/m² (10.2 oz/sq ft) +13% / -10%	4300 g/m² (14.1 oz/sq ft) +13% / -10%
<b>Thickness (mm.) (in)</b>	ISO 1765:1986	2.30 mm (0.09 in)	3.00 mm (0.12 in)
<b>Light Fastness (Grey scale: 1-5)</b>	EN ISO 4892:2006 (exterior)	>4/5	>4/5
<b>Light Fastness (Blue scale: 1-8)</b>	EN ISO 105B02:2001 (interior)	>7/8	>7/8
<b>Dimensional Stability %</b>	EN ISO 23999:2012	≤0.25%	≤0.25%
<b>Residual Indentation</b>	EN ISO 24343-1:2012	<0.10 mm (<0.003 in)	<0.10 mm (<0.003 in)
<b>Castor Chair Test</b>	EN 985:2002	Intensive use	Intensive use
<b>Sound Insulation</b>	EN ISO 10140-3:2011	12 dB	13 dB
<b>Thermal Resistance</b>	EN 12667:2001	< 0.15m² K/W	< 0.15m² K/W
<b>Static Electricity</b>	EN 1815:1997	< 2 kV	< 2 kV
<b>Slip Resistance</b>	EN 13893:2003	>0.4	>0.4
<b>Slip Resistance</b>	DIN 51130:2014	R10	R10
<b>Slip Resistance</b>	ASTM C1028-96 Static Coefficient	Wet: 0.79; Dry: 0.86	Wet: 0.79; Dry: 0.86
<b>Fire Classification</b>	EN 13501-1:2007	Bfl-S1	Bfl-S1
<b>Fire Classification</b>	ASTM E648 (NFPA 253)	Class 1	Class 1
<b>Antibacterial activity</b>	ASTM E 2180-18 ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
<b>Roll Width</b>	-	200 cm 78.740 in	
<b>Roll Length</b>	-	10 lm (32.81ft) 20 lm (65.62 ft)	
<b>CE Certificate</b>	EN 14041:2004	2895-CPR-SH00981	2895-CPR-SH00981
<b>Use Classification</b>	EN 1307:2014	Heavy Commercial	
<b>Tile Dimensions</b>	<div style="display: flex; justify-content: space-around; align-items: flex-end;"> <div style="text-align: center;"> <p>Square</p> <p>50cm/100cm</p> </div> <div style="text-align: center;"> <p>Plank</p> <p>25cm</p> </div> <div style="text-align: center;"> <p>Brick</p> <p>50cm</p> </div> <div style="text-align: center;"> <p>Diamond</p> <p>50cm</p> </div> <div style="text-align: center;"> <p>Hexagon</p> <p>61.4cm</p> </div> <div style="text-align: center;"> <p>E. Triangle</p> <p>50cm</p> </div> <div style="text-align: center;"> <p>I. Triangle</p> <p>50cm</p> </div> <div style="text-align: center;"> <p>Trap</p> <p>61.4cm</p> </div> <div style="text-align: center;"> <p>Arcade</p> <p>75cm</p> </div> </div>		

Some of the test and certifications present in this TDS can be found under the name Fitnice Floor



ISO 9001:2015 and  
ISO 14001:2015  
certified company



EPD registration number S-P-01029 [www.environdec.com](http://www.environdec.com)